

Single Phase Hybrid Inverter

ALPHA PRO 3kw-24V Single MPPT



LCD Screen



Dual Output Inverter for Normal Load and Smart Load



DC couple and AC couple to retrofit existing solar system



4000W Load Capacity



5500W Solar Capacity



2 Years Warranty

MODEL	ALPHA PRO 3KW-24V
RATED POWER	4000VA/4000W
INPUT	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
OUTPUT	
AC Voltage Regulation (Batt. Mode)	230VAC ± 10%
Max Output/Surge Power	4000W/8000W
Efficiency (Peak)	90% ~ 93%
Transfer Time	10 ms (For Personal Computers) 20 ms (For Home Appliances)
Waveform	Pure sine wave
BATTERY	
Battery Voltage	24 VDC
Floating Charge Voltage	27 VDC
Overcharge Protection	33 VDC
SOLAR CHARGER & AC CHARGER	
Solar Charger type	MPPT
Maximum PV Array Power	5500W
MPP Range @ Operating Voltage	60 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum PV Input Current	27A
Maximum Solar Charge Current	120A
Maximum AC Charge Current	100A
Maximum Charge Current	120A
PHYSICAL	
Dimension, D x W x H (mm)	115 x 300 x 435
Net Weight (kgs)	9KG
Communication Interface	USB/RS232/RS485/WiFi/Dry-contact
OPERATING ENVIRONMENT	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C
Warranty	2 Year