


Single Phase Hybrid Inverter

Galaxy 7G PRO 10Kw-48V Triple MPPT



Colorful touch LCD, IP65 protection degree



AC couple to retrofit existing solar system



Max. 16 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel



Max. charging/discharging current of 250A



6 time periods for battery charging/discharging



Support storing energy from diesel generator

Model	Galaxy 7G PRO 10 kw-48V
Battery Input Data	
Battery Type	Lead-acid or Lithium-ion
Battery Voltage Range (V)	40~60
Max. Charging Current (A)	250
Max. Discharging Current (A)	250
Number of Battery Input	1
Charging Strategy for Li-Ion Battery	Self-adaption to BMS
PV String Input Data	
Max. DC Input Power (W)	18000
Max. PV Input Voltage (V)	500
Start-up Voltage (V)	125
MPPT Voltage Range (V)	150V-425V
Rated PV Input Voltage (V)	370
Max. Operating PV Input Current (A)	26+26+26
Max. Input Short-Circuit Current (A)	44+44+44
No.of MPP Trackers	3
No.of Strings per MPP Tracker	2+2+2
AC Input/Output Data	
Rated AC Input/Output Active Power (W)	12000
Max. AC Input/Output Apparent Power (VA)	13200
Rated AC Input/Output Current (A)	54.6/52.2
Max. AC Input/Output Current (A)	54.6/52.2
Max. Continuous AC Passthrough (grid to load) (A)	60A
Peak Power (off grid)	2 time of rated power, 10 S
Power Factor Adjustment Range	0.8 leading to 0.8 lagging
Rated Input/Output Voltage/Range (V)	220/230 0.85Un-1.1Un
Rated Input/Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65
Grid Connection Form	L+N+PE
Total Current Harmonic Distortion THDi	<3% (of nominal power)
DC Injection Current	<0.5% In
Efficiency	
Max. Efficiency	97.6%
Euro Efficiency	96.5%
MPPT Efficiency	>99%
Equipment Protection	
Integrated	DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection AC Output Overvoltage Protection, AC Output Short Circuit Protection, Thermal Protection DC Terminal Insulation Impedance Monitoring, DC Component Monitoring, Ground Fault Current Monitoring Power Network Monitoring, Island Protection Monitoring, Earth Fault Detection, DC Input Switch Overvoltage Load Drop Protection, Residual Current (RCD) Detection, Surge protection level
Surge Protection Level	TYPE II(DC), TYPE II(AC)
Interface	
Communication Interface	RS485/RS232/CAN
Monitor Mode	GPRS/WIFI/Bluetooth/4G/LAN(optional)
General Data	
Operating Temperature Range (°C)	-40 to +60°C, >45°C Derating
Permissible Ambient Humidity	0-100%
Permissible Altitude	2000m
Inverter Topology	Non-Isolated
Over Voltage Category	OVC II(DC), OVC III(AC)
Type of Cooling	Intelligent Air Cooling
Noise (dB)	<45
Communication with BMS	RS485; CAN
Weight (kg)	35.6
Cabinet Size (WxHxD mm)	420×670×233 (Excluding Connectors and Brackets)
Ingress Protection(IP) Rating	IP65
Installation Style	Wall-mounted
Grid Regulation	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/NBR16150
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2
Warranty	6 Years/10 Years the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to